

TM620A75 SERIES**(24.3" diameter)****SPECIFICATIONS****TM500A75 - 450 (50.0 HP 1740 RPM)**

V (ft/min)	923	726	576	453
BP (lbs)	1786	2271	2863	3640
T ' lbs.	1793	2279	2873	3654

TM620A75 - 440 (40.0 HP 1740 RPM)

V (ft/min)	923	726	576	453
BP (lbs)	1432	1821	2295	2918
T ' lbs.	1450	1843	2324	2954

TM620A75 - 430 (30.0 HP 1740 RPM)

V (ft/min)	923	726	576	453
BP (lbs)	1074	1365	1721	2189
T ' lbs.	1087	1382	1743	2216

TM620A75 - 425 (25.0 HP 1740 RPM)

V (ft/min)	923	726	576	453
BP (lbs)	895	1137	1435	1824
T ' lbs.	906	1152	1452	1846

TM620A75 - 620 (20.0 HP 1150 RPM)

V (ft/min)	615	484	384	302
BP (lbs)	1074	1365	1721	2189
T ' lbs.	1087	1382	1743	2216

TM620A75 - 815 (15.0 HP 875 RPM)

V (ft/min)	462	363	288	226
BP (lbs)	1074	1365	1721	2189
T ' lbs.	1087	1382	1743	2216

V = Velocity **BP** = Belt Pull **T** = Torque **RPM** = Internal Electric Motor RPM

NOTE: All drum motors are available in all standard voltages and are electrically reversible. Other belt speeds and face widths are available. *Please consult Van der Graaf: +1 905 793-8100.*

