

TM800A130 SERIES**(31.5" diameter)****SPECIFICATIONS****TM800A130 - 4200 (200.0 HP 1740 RPM)**

V (ft/min)	1077	914	745
BP (lbs)	5715	6736	8786
T ' lbs.	7501	8841	11531

TM800A130 - 4180 (180.0 HP 1740 RPM)

V (ft/min)	1077	914	745
BP (lbs)	5144	6063	7908
T ' lbs.	6751	7957	10378

TM800A130 - 4150 (150.0 HP 1740 RPM)

V (ft/min)	1077	914	745
BP (lbs)	4287	5053	6590
T ' lbs.	5626	6631	8648

TM800A130 - 6120 (120.0 HP 1150 RPM)

V (ft/min)	1091	917	703	597	458
BP (lbs)	3462	4117	5369	6328	8253
T ' lbs.	4543	5402	7046	8305	10831

TM800A130 - 6100 (100.0 HP 1150 RPM)

V (ft/min)	1091	917	703	597	458
BP (lbs)	2885	3430	4474	5273	6878
T ' lbs.	3786	4502	5872	6921	9026

TM800A130 - 675 (75.0 HP 1150 RPM)

V (ft/min)	1091	917	703	597	458
BP (lbs)	2116	2516	3281	3867	5044
T ' lbs.	2776	3301	4306	5075	6619

V = Velocity **BP** = Belt Pull **T** = Torque **RPM** = Internal Electric Motor RPM

NOTE: All drum motors are available in all standard voltages and are electrically reversible. Other belt speeds and face widths are available. *Please consult Van der Graaf: +1 905 793-8100.*

