

TM600A100 Drum Motor

75.0 HP

V (ft/min) M/G	925 4/S2	729 4/S2	578 4/S2	463 4/S2	364 4/PL2
Belt Pull (lbf)	2550	3235	4085	5000	6479
Drum RPM	148	117	93	74	58

60.0 HP

V (ft/min) M/G	463 4/S2	364 4/PL2	303 4/PL2
Belt Pull (lbf)	4076	5183	6220
Drum RPM	74	58	49

50.0 HP

V (ft/min) M/G	364 4/PL2	370 6/S2	303 4/PL2	243 4/PL2
Belt Pull (lbf)	4319	4251	5183	6479
Drum RPM	58	59	49	39

40.0 HP

V (ft/min) M/G	364 4/PL2	303 4/PL2	243 4/PL2
Belt Pull (lbf)	3455	4146	5183
Drum RPM	58	49	39

30.0 HP

V (ft/min) M/G	364 4/PL2	303 4/PL2	243 4/PL2
Belt Pull (lbf)	2592	3110	3887
Drum RPM	58	49	39

25.0 HP

V (ft/min) M/G	364 4/PL2	303 4/PL2	243 4/PL2
Belt Pull (lbf)	2160	2592	3239
Drum RPM	58	49	39

20.0 HP

V (ft/min) M/G	243 6/PL2	182 6/PL2	146 6/PL2
Belt Pull (lbf)	2592	3455	4313
Drum RPM	39	29	23

V = Belt Speed (ft/min)

M/G = Motor/Gear Reducer Configuration (at rated horsepower)

